

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number  
**WO 2005/045295 A1**

(51) International Patent Classification<sup>7</sup>: F16L 1/16, 1/24

(21) International Application Number:  
PCT/EP2004/009949

(22) International Filing Date:  
7 September 2004 (07.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0326052.8 7 November 2003 (07.11.2003) GB

(71) Applicant and

(72) Inventor: BAGHERNEJAD, Massoud [GB/GB]; Flat 8,  
Hilton House, Amherst Road, London W13 8NF (GB).

(74) Agent: ROUSE PATENTS; Windsor House, Cornwall  
Road, Harrogate HG1 2PW (GB).

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

(54) Title: METHOD AND APPARATUS FOR LAYING A PIPELINE



(57) Abstract: A method and apparatus for laying an underwater pipeline. The method includes the steps of constructing lengths of pipeline by endwise connection of a plurality of pipe segments (12) and securing bend restriction means (18) along the length of said lengths of pipeline. The bend restriction means (18) is arranged to prevent the lengths of pipeline from bending by more than a predetermined maximum amount. Flotation means (28) are secured to the lengths of pipeline such that the lengths of pipeline are held adjacent the surface of the ocean and the lengths of pipeline are towed to the desired location. Each length of pipeline is connected to an adjacent length of pipeline and the flotation means (28) are released from each length of pipeline so that the length of pipeline sinks to the ocean floor.